

| Model | 65IN | 86IN | 8IN |
|--|------------------------------|------------------------------|------------------------------|
| Display | | | |
| Active Screen Size | 65" | 86" | 98" |
| Backlight | LED | LED | LED |
| Display Ratio | 16:9 | 16:9 | 16:9 |
| Resolution | 3840 x 2160 (4K) | 3840 x 2160 (4K) | 3840 x 2160 (4K) |
| Brightness | 250-500cd/m ² | 250-500 cd/m ² | 500 cd/m ² |
| Dynamic Contrast | 4000:1 | 4000:1 | 4000:1 |
| Response Time | 8ms | 8ms | 8ms |
| Viewing Angle | 178° | 178° | 178° |
| Lifetime Hours | ≥ 50,000 hours | ≥ 50,000 hours | ≥ 50,000 hours |
| Continuous Run Time | 24/7 | 24/7 | 24/7 |
| Power | | | |
| Max Power Consumption | ≤200W | ≤450W | ≤700W |
| Speakers | | | |
| Max Power Output | 10W X 2 (20W) | 10W X 2 (20W) | 10W X 2 (20W) |
| Transportation/Storage | | | |
| Storage Humidity | 20~90%RH (non-condensing) | 20~90%RH (non-condensing) | 20~90%RH (non-condensing) |
| Working Humidity | 20~80%RH (non-condensing) | 20~80%RH (non-condensing) | 20~80%RH (non-condensing) |
| Installation Method | Wall-mounted or Mobile Stand | Wall-mounted or Mobile Stand | Wall-mounted or Mobile Stand |
| VESA Mount Pattern | 600x400mm | 800x400mm | 800x600mm |
| Net Weight (lbs) | 62 | 113 | 190 |
| <p>Note: Images and specifications can be changed without prior notice for the product enhancement.</p> | | | |