



Introduction

This is a new fixed 4K60@ (4:4:4) HDMI matrix switcher with 4 HDMI2.0 inputs and 4 HDMI2.0 outputs, the resolution can up to 4K60Hz and all ports are HDCP2.2 compliant. With the friendly user control methods by IR remote control, 2-Press push buttons with background blue light, WEB GUI, APP and RS232/UDP commands, this matrix switcher can work with the Blu-Ray Players, Set-Top boxes, Home Theater, and game consoles etc. HDMI input sources to route to the HDMI displays, it has been widely used in different audio visual applications.

Features


- ➤ 4 HDMI2.0 inputs
- ➤ 4 HDMI2.0 outputs with one independent 3.5mm/SPDIF audio
- Supports HDMI2.0, HDCP2.2
- The resolution can up to 4K@60Hz (4:4:4) at 600 MHz
- Supports LPCM 7.1CH, Dolby TrueHD, Dolby Digital and DTS-HD Master Audio
- Supports 3D, HDR Video, Deep Color (12-bit).
- Supports IR remote control(IR remote control codes are available)
- Supports smart EDID management, including 4-output EDID, 15 internal EDID.
- Supports RS-232 and TCP/IP Control(WEB GUI, APP and IR remote)
- > Supports 2-press push buttons control with blue lights
- Supports to rename the inputs and outputs, scenes

Specification


Name	4K60 4x4 HDMI2.0 Matrix Switcher
Resolutions	480i, 576i, 480p, 576p, 720p, 1080i, 1080p@24/30/50/60Hz, 4K@60Hz
Input ports	4 * HDMI, 1* RS-232(control), 1 * RJ-45(control)
Output ports	4 * HDMI, 1* RS-232(control),1*3.5mm/SPDIF audio
ESD Protection	\pm 8kV (Air-gap discharge), \pm 4kV (Air-gap discharge)
Controlling	IR remote control, front buttons control, RS232, UDP, HTTP, TCP/IP
Power	DC: 12V 2A
Data rate	18 Gbps
Weight	4kg



Connection diagram



Product Dimension



Email: info@geniuspresentation.com