

**Features**

- High quality birch plywood cabinet
- Built-in 70V/100V transformer, together with 8Ω direct capability
- Speech/Music mode available
- Multiple mounting available



**Specifications:**

Model	GEN-CS34	GEN-CS38	GEN-CS316
Driver	4 x 3" Full Range Driver	8 x 3" Full Range Driver	16 x 3" Full Range Driver
Power	100W; 320W(PEAK)	160W; 640W(PEAK)	270W; 880W(PEAK)
Frequency Response	40Hz-20kHz		
Dispersion (H x V)	160° x 45°		
Max SPL @ 1m	124dB/126dB(PEAK)		
Sensitivity (1W @ 1m)	96dB		
Nominal Impedance (Ohm)	8 Ω		
Grille	Steel power coating		

Features

- Application in Meeting Rooms, Conference Room, Small Auditorium
- Full range Column speaker
- 5.5 in woofer and 1 in tweeter



Specifications:

Model	GEN-CS16T
Frequency response	20-20KHz
Max SPL	127dB
Dispersion (H x V)	160° x 60°
Drivers	16x 1" HF, 4 x 5.5" LF
Sensitivity	102dB
Power	500 Watt, 2000 Watt (Peak)
Nominal Impedance	8Ω
Construction	ABS