

Features

- Coaxial full range ceiling loudspeaker
- Powder coated perforated steel grille with dust protection and Zinc plated steel back can
- With line transformer and 70V/100V tapping switch
- Four Pole Phoenix connector (Loop-Through wiring)



Specifications:

Model	GEN-CS4P	GEN-CS5P	GEN-CS6P
Rated power (100V)	1.75W, 3.75W, 7.5W	3.75W, 7.5W, 15W, 30W	3.75W, 7.5W, 15W, 30W
Rated power (70V)	1.9W, 3.75W, 7.5W, 15W, 30W	1.9W, 3.75W, 7.5W, 15W, 30W	1.9W, 3.75W, 7.5W, 15W, 30W
Impedance	2.7KΩ/1.3KΩ/670Ω/330Ω	2.7KΩ/1.3KΩ/670Ω/330Ω/165Ω	2.7KΩ/1.3KΩ/670Ω/330Ω/165Ω
Dispersion	160°	160°	160°
Sensitivity (1W/1M)	89dB	89dB	89dB
Maximum sensitivity (W/1M)	106dB	106dB	106dB
Frequency response (-10dB)	50-20KHz	50-20KHz	50-20KHz
Drivers LF HF	4"x1 1"x1	5"x1 1.5"x1	6.5"x1 1.5"x1
Power Handling	40W RMS, 160W PEAK	60W RMS, 120W PEAK	60W RMS, 200W PEAK

Features

- Application in Meeting Rooms, Conference Rooms
- Full range ceiling speaker
- 6.5 in woofer and 1 in tweeter



Specifications:

Model	GEN-CS7
Frequency response	20-20KHz
Max SPL	110dB/118dB (Peak)
Dispersion	120°
Drivers	1x 1" HF, 1 x 6.5" LF
Sensitivity	98dB
Power	80 Watt, 120 Watt (Peak)
Transformer Taps	100V/70V-80/40/20/10 Watt
Nominal Impedance	8Ω
connectors	4 Pin Phoenix (Including 2 pin Out)
Construction	ABS with Metal Back Can