

1.5IN

All-In-One LED

DATASHEET



Features:

- Ultra-light & Ultra-thin: Border thickness less than 19mm.
- Wide-angle Camera:99° diagonal,87° horizontal, 49° vertical.
- Supports WiFi 6 for high-speed operation (2.4G and 5G bands).
- Supports meeting check-in through personnel identification technology.

Technical Specification

Model

Model	1.5IN
-------	-------

Parameters

Pixel Pitch	1.56mm
Pixel Configuration	1R1G1B
LED Type	SMD 3 IN 1
Brightness (Max)	600 nit
Viewing Angle (H/V°)	160°/160°
Pixel Density	409,600 pixels/m ²
Module Size	300mm×168.75mm
Display Resolution(W×H)	1920×1080
Visible Area (H x V)	3000mm×1687.5mm
Overall Size (W×H×D)	3013.3mm × 1823.7mm × 18.8mm
Weight	120kg±0.5
Display Size	136 inch
Cabinet Material	Die-cast aluminum
IP Rating	Front IP30/Rear IP30

Operating Temperature/ Humidity	-10℃~+40℃/10%~90%RH
Storage Temperature/ Humidity	-20℃~+60℃/10%~60%RH
Gray Scale	14bits
Contrast Ratio	4000:1
Refresh Rate	3840 Hz
Input Voltage	AC100~240V (+/-10%)
Lifetime	100000 Hours
Input Power (Avg)	1000W
Installation Mode	Movable base/Wall mounted(customizable)
Maintenance Mode	Front Maintenance
System / Storage Memory	8G / 64G
Control Interface	RJ45/RS232x1,USB3.0x4,Bluetoothx1,WIFI6x1,Light perceptionx1,Infrared remote controlx1
Video Interface	HDMIx2 (1 in 1 out), TYPE-C/DP x1
Audio Interface	Built-in 4x15W speakers,3.5mm Line Out x1
System	Android 11/Windows 11 (Optional)