

1.5IN

All-In-One LED

DATASHEET



Features:

- Ultra-light & Ultra-thin: Border thickness less than 19mm.
- Wide-angle Camera:99° diagonal,87° horizontal, 49° vertical.
- Supports WiFi 6 for high-speed operation (2.4G and 5G bands).
- Supports meeting check-in through personnel identification technology.
- Available in size 130 inch and 136 inch

Technical Specification

Model

Model	1.5IN
-------	-------

Parameters

Pixel Pitch	1.56mm
Pixel Configuration	1R1G1B
LED Type	SMD 3 IN 1/COB/QCOB
Brightness (Max)	1000 nits
Viewing Angle (H/V°)	160°/160°
Pixel Density	409,600 pixels/m ²
Display Resolution(W×H)	1920×1080
Input Ports	HDMI 2.0x2 ,TYPE-C/DP ×1
Output Ports	HDMI 2.0 x 1, 3.5mm Line Out/SPDIF ×1
WIFI	Yes
Weight	120kg±0.5
Display Size	130/136 inch
Cabinet Material	Die-cast aluminum
IP Rating	Front IP30/Rear IP30

Operating Temperature/ Humidity	-10℃~+40℃/10%~90%RH
Storage Temperature/ Humidity	-20℃~+60℃/10%~60%RH
Gray Scale	14bits
Contrast Ratio	8000:1
Refresh Rate	3840 Hz
Input Voltage	AC100~240V (+/-10%)
Lifetime	100000 Hours
Input Power (Avg)	600W
Installation Mode	Movable base/Wall mounted(customizable)
Maintenance Mode	Front Maintenance
System / Storage Memory	3.0 GHz quad core processor/8G / 64G
Control Interface	RJ45/RS232x1,USB3.0x4,Bluetooth,WIFI6x1, 1G Ethernet Port, Light perceptionx1,remote control
Video Interface	HDMI 2.0x2 INPUT, HDMI 2.0 x 1 OUTPUT, TYPE-C/DP ×1
Audio Interface	Built-in 4x15W speakers,3.5mm Line Out ×1
System	Android 11/Windows 11 (Optional)